

AIRMAX VS® CONNECTOR SYSTEM

A FLEXIBLE HIGH SPEED SIGNAL CONNECTOR DESIGN




AIRMAX VS® CONNECTOR SYSTEM INFORMATION


Documentation

- AirMax VS® Connector Systems for Data
- AirMax VS® Connector Systems for Telcos
- AirMax VS® Storage Bridge Bay Applications
- AirMax VS® Orthogonal Connectors
- AirMax VS® Power Connectors
- Hard Metric High Power Connectors

BACK PANEL RECEPTACLE




ORTHOGONAL MIDPLANE



HIGH POWER CONNECTORS



BACK PANEL-HEADER



CO-PLANAR



AIRMAX VS® CONNECTOR SYSTEM

A FLEXIBLE HIGH SPEED SIGNAL CONNECTOR DESIGN



- The first shieldless high speed connector
- Speeds of up to 12.5Gb/s
- Very low insertion loss and crosstalk
- Hard Metric (HM) equipment design practice
- High signal density for a given daughter card pitch
- Numerous 3, 4, and 5 pair products tooled, both genders
- Backpanel, Coplanar, Mezzanine, Orthogonal and I/O products
- Press-fit “eye of needle” contacts

Backplane

Minimum Card Slot Pitch (mm)	Column Spacing (mm)	Differential Signal Pairs per Column	Signal Density (pairs/inch)
16.7	3.0	3	25
16.7	2.0	3	37.5
20	3.0	4	33.9
20	2.0	4	50.8
25	3.0	5	42.3
25	2.0	5	63.5

Orthogonal

Orthogonal Pairs	Grid	Signal pairs Description	Col Pitch mm	Slot width mm
16	4X4	Airmax VS Orthogonal	4.2	20